



Via Caciagli 11 – Zona Industriale Terrafino 50053 Empoli  
Tel 0571 930032 – 930065 fax 930056 viva@vivasrl.it

### HAND CAST STRETCH FILM 23MIC

Topics	Results
1) Description:	Stretch film roll 50cm 23 micron
2) Raw material:	LLDPE Cast Stretch Wrap Film Polyethylene 23my Components : Paper core Rigid width 50mm
3) width roll:	50 cm $\pm$ 1% ( SP METHOD)
4) Film Length :	250mt $\pm$ 8% ( SP METHOD)
5) Color :	Natural <b>Clear</b>
6) Thickness :	23my $\pm$ 1.5my ( SP METHOD)
7) Density:	0.918 gr/cm <sup>3</sup> ( ISO 1183 A METHOD)
8) Tensile strenght MD	55 Mpa ( ASTM D882 )
9) Tensile strenght TD	28 Mpa ( ASTM D882 )
10) Elongation at break %	150-180 % MD ( SP METHOD)
11) Fusion point	121 C°
12) Impact strenght	110 gr ( ASTM 1709)
11) Packing :	6 Bobine per cartone

**Articolo : 1390**

**Marca: VIVA**

**Nome del Prodotto: Cast Stretch film**

Product mechanical and physical properties are given by considering values of raw material supplier's product specification for 23 micron film at 25+ C° and 50% of humidity rate.

The values estimated are related to the samples analysed but can be different on the mass production.