

Masking Tapes



Items: 60SF

Backing: Impregnated Paper medium creped

Adhesive: Natural rubber

Colour: Ivory, Yellow

- * FSC Mix Paper
- * Suitable for general purpose masking application
- * It can be used up to 60°C
- * Suitable for indoor painting masking for wall, wood, metal, furniture.
- * Removable until 4 days without leaving any residue



Material Information

Code	Width (mm)	Length (m)	Temperature Resistance (°C)
60SPP	25,30,38,50	50	60 °C for 60 minutes

Technical Information

Total Weight		Total Thickness		Adhesion to steel plate		Tensile Strength		Elongation	
85 gr/mq	±5%	120 µ	±10%	> 200 gr/cm		>2,4 Kg/cm		> 6%	

Storage Conditions

- We recommend a storage temperature between 18 and 30 °C.
- The product should not be directly exposed to heat or humidity.
- The product should be conditioned to room temperature before use.

All the above-mentioned values in Technical Information are to be considered as average values of our standard production and cannot be taken as product specifications. The products can present a ±2% tolerance in width and length
For DIY TAPES we recommend all our customers to make sure that the products is acceptable for application through preliminary test.

Certified Systems

UNI-EN ISO 9001:2015 n° IT314901

Revisited: 01/04/2024

