

3M Construction & Home Improvement Markets

Product Information Sheet

Issue : January 2019

Scotch Extremium No residue duct tape

Description



Scotch Extremium No residue duct tape removes with no residue from most opaque surfaces for up to six months after application. The Scotch® no residue technology is ideal for temporary long duration applications, both indoor and outdoor. This is a high strength duct tape without adhesive transfer and messy cleanup after removal.

Product Characteristics	
Backing	Waterproof, polyethylene film over cloth scrim
Adhesive	Natural and synthetic Rubber-based adhesive
Standard Roll length	48mm x 18.2m (20 yards)
Temperature resistance	Up to 93°C
Color	Charcoal grey

Typical Physical Properties	value	Method
Total thickness	280 µm	ASTM D-3652
Adhesion to steel	5.7 N/cm	ASTM-D3330
Tensile strength	61 N/cm	ASTM-D3759
Elongation at break	21 %	ASTM-D3759

The values displayed are the result of illustrative lab test measures made according to the indicated external norm and shall not be considered as a commitment from 3M

Storage

To obtain best performances, store this product under normal condition of 21°C and 50% relative humidity in the original packaging and use it within one year from date of purchase.

Warning

Apply above 10°C and up to 70°C-

Do not use on wallpaper or other delicate surfaces. Do not use on poorly bonded surfaces

In case of doubt, test before use

Do not use on flues, chimneys, mufflers or tailpipes.

3M Construction & Home Improvement Markets

Product Information Sheet

2/2

Features/advantages/Benefits

Features	Advantages	Benefits
Rubber adhesive	Instant adhesion	Stick easily to the surface
	Very Good holding power Long lasting	Helps resist lifting or curling, help reduce work
No residue	Scotch® technology to ensure proper bond of the adhesive with the backing to avoid adhesive residue up to 6 months when removal	Allows long lasting temporary repairs without spending time and hassle removing adhesive residues
PE over cloth scrim	Hand tearable in both side Water proof backing* Temperature resistance up to 93°C	Easy handling and usage Indoor and outdoor usage
Narrow scrim	Better resistance	Larger range of application
	High tensile strength for demanding application	

*Not suitable for water leaks repairs.



Important notice :

The use of the 3M product described within this document assumes that the user has read and understood the user notice. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected purpose.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation