

55790, 55791, 55792
Powerbond Ultra Strong

Product Description

- tesa Powerbond® Ultra Strong is a very strong double sided and self adhesive tape
- Newly developed synthetic rubber adhesive with outstanding holding power
- Strong and reliable PE-foam backing.
- For long-lasting, secure and fast interior- and exterior fixing of multiple objects and applications (Not UV-resistant. Protect from direct contact with water)*
- Holds on most smooth, sufficient firm surfaces*
- Optimum mounting temperature: 20-25°C (min 10°C)
- Holding power: 100kg/m **

Please note:

- The total weigh per meter cannot be applied in one piece
- Single objects should not be heavier than 6kg**
- Each object should be flat with a maximum depth of 10mm

Dimensions

IBNR	Dimensions
55790	pads
55791	1,5m : 19mm
55792	5m : 19mm

Technical Data

Colour: white	Thickness: 1,1 mm
Adhesive: Synthetic rubber	Peel adhesion / steel: >10* N/cm
Backing: PE foam (white)	Storage time: 1 year (in closed box)
Liner: Double sided siliconised paper	

*The holding power can be limited due to several factors: characteristics of the surface, dirt and dust on applied surfaces, cleaning before application. Equally applied pressure for total area is difficult for end-consumer. Touching of the surface/ fixing area before application can affect the holding power.

**tesa® products are tried and proven quality products which are constantly subjected to strict controls. You will achieve optimum results if you work on dry, dust and grease-free surfaces. Since we have no influence on your individual working conditions or the properties of all different kinds of material, no claim may arise from the statements made in this product information.

Parameters of the specification / 15/08/2013



tesa AG

Quality
management

Internal page - Product information

Date of last Version:	Date of Alteration	Subject of Alteration	Kst / PM	Kst. / F & E
15.08.2013	-	-	8310/ RW	8320/ TS

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

<http://www.tesa.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.