



Il marchio della gestione forestale responsabile



Rismacqua. Carte e cartoncini multiuso dai colori tenui per l'ufficio, la casa, la scuola e il tempo libero. Ideali per tutti i sistemi di copiatura e stampa (inkjet, laser, offset...). Tutti i colori sono resistenti alla luce. Le carte sono ricavate da impasti a base di cellulose selezionate chlorine free (ECF) non provenienti da foreste vergini.

Collo di spedizione:

- Scatola contenente 5 risme dello stesso colore.

Rismacqua. Multipurpose, soft-coloured paper and cardboard for office, home, school uses and leisure. Suitable for all kind of photocopying and printing (inkjet, laser, offset...). All colours are light-resistant. The paper is obtained from selected chlorine free (ECF) cellulose, which does not derive from virgin forests.

Packaging:

- Carton box containing 5 reams of the same colour.

RISMACQUA

A4 21x29,7 cm

300 fogli/sheets
90 g/m²

200 fogli/sheets
140 g/m²

125 fogli/sheets
200 g/m²

A3 29,7x42 cm

300 fogli/sheets
90 g/m²

200 fogli/sheets
140 g/m²

125 fogli/sheets
200 g/m²

- 110 avorio
- 07 giallo chiaro
- 02 camoscio
- 05 salmone
- 10 rosa
- 06 lilla
- 08 celeste
- 09 verde chiaro
- 12 ghiaccio

A66Q304

A65Q204

A67Q104

A66Q313

A65Q213

A67Q113

A662304

A652204

A672104

A662313

A652213

A672113

A66R304

A65R204

A67R104

A66R313

A65R213

A67R113

A66S304

A65S204

A67S104

-

-

-

A66S304

A65S204

A67S104

A66S313

A65S213

A67S113

A669304

A659204

A679104

A669313

-

A679113

A66T304

A65T204

A67T104

A66T313

A65T213

A67T113

A66P304

A65P204

A67P104

A66P313

A65P213

A67P113

A66U304

A65U204

A67U104

A66U313

-

A67U113

RISMALUCE / RISMACQUA SCHEMA TECNICA – TECHNICAL CHART

Characteristic	Standard	Unit	rismaluce / acqua 90 g.	rismaluce / acqua 140 g.	rismaluce / acqua 200 g.
Grammage / Grammatura	ISO 536	g/m ²	90±5%	140±5%	200±5%
Thickness / Spessore	ISO 534	µm	116±5%	172±5%	228±5%
Bulk / Mano	ISO 534	cm ³ /g	1,29	1,23	1,14
CIE dL*	ISO 2469-70	-	45-92	45-92	45-92
burst index	ISO 2758	kPa*m ² /g	2,8	3,0	2,3
ash content/ceneri	ISO 1762	%	16-20	16-20	16-20
Roughness/Liscio Bendtsen FELT SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Roughness/Liscio Bendtsen WIRE SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Absolute Humidity	ISO 287	%	6.0±1.0	6.0±1.0	7.0±1.0

1. Paper type: MULTIPURPOSE PAPER / OFFICE PAPER
2. Degree of processing: UNCOATED PAPER
3. Specifications (A3 = cm 29,7x42 – A4 = cm 21x29,7)
4. Fiber type and composition: 25% LONG FIBERS; 75% SHORT FIBERS (BLEACHED CHEMICAL PULP)
5. Manufacturer name: CARTOTECNICA FAVINI S.R.L.
6. COLOURED PAPER

Data / Date: 3.08.2017

Cartotecnica Favini S.r.l.

Direttore Generale
Andrea Bertone

