

PRODUCTS' INFORMATION

date : 11 July, 2018



1.5mm 



PRODUCT CODE	Artline Concrete Marker (EKPR-CRM)		
CATEGORY	Instant drying permanent marker for special purpose		
USAGE	Concrete, Brick and Rough surfaces  CONCRETE  BRICK  ROUGH SURFACES 		
REFILLABILITY	Non-refillable		
FEATURES	Writes on any rough surfaces. Long lasting nib Instant draying.		
TOXIC INK CONTENTS	Xylene free		

* COMPOSITION

INK	TYPE	Alcohol based dyestuff ink
	COLOURS	1 colour (Black)
	CONTENTS	5.5 gr.
HOLDER		PP
INK RESERVOIR		PP / PE fibre
CAP		PP
BODY		Aluminium
NIB	SHAPE	Bullet style
	MATERIAL	Acrylic fibre

* QUALITY CONTROL

REGULATION	Adapted to the BS safety cap standard and RoHS.
PRODUCTION LOT	Inkjet printing on the bottom face of barrel.

PRODUCTS' INFORMATION

date : 11 July, 2018



* PERFORMANCE

WRITING WIDTH		1.5 mm
WRITING DISTANCE		600m WRITING TEST METHOD : angle 65°weight 100g, speed 20 cm per sec., on paper 60-70m by hand writing WRITING TEST METHOD : angle 65°weight 100g, speed 20 cm per sec., on concrete
DRYING TIME	NIB	5 minutes
	WRITING LINE	Less than 60 seconds on PET film
WATER RESISTANCE		Very good
FADE PROOF		Good
CAUTIONS		* Marker is to be used for marking and drawing only. Do not use for other purposes. * Do not drop or shake hard to avoid ink leaking. * Ink (stain) on cloth may not be removed. * Must be kept out of reach of children. * Harmful if swallowed. Vapor harmful. Avoid contact with eyes or skin. If swallowed and contacted with eyes, call physician immediately. * Keep room well ventilated, when in long use. * Keep capped horizontally when not in use. * Flammable. Do not use or store near heat of flame and throw marker into fire.