

tesapack® paper ecoLogo® – 04313

- Sturdy and environmental-friendly
- Strong adhesion
- Highly tear-resistant, unbleached paper backing
- Good sealing security
- High-class appearance of packaging

Ecological features:

- Tape: 60% bio-based
- Core: 100% recycled cardboard
- Contour cuff: 80% recycled cardboard
- Solvent-free adhesive

Main Application

- For sealing cartons, boxes and envelopes

Technical Data & Properties

Dimensions	25m, 50m / 38mm, 50mm
Product structure	Single-sided
Colour	Brown
Adhesion/Steel	7,5 N/cm
Type of Backing	Paper
Total Thickness	107 µm
Tensile Strength	50 N/cm
Elongation at break	8%

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Exemplary representation



05054



57180



55337

IBNR's

IBNR	Article Description
05054	TESAPACK PAPER ECOLOGO 25M :38MM CONTOUR CUFF
55337	TESAPACK PAPER ECOLOGO 3X 50M:50MM SHRINK TOWER
57180	TESAPACK PAPER ECOLOGO 50M:50MM LABEL

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.