

PRODUCT INFORMATION

date :11 July, 2018



2.3mm 



PRODUCT CODE	Artline Builders Marker (EKPR-BDM)
CATEGORY	Instant Drying Paint Marker for supecial purpose (Valve Action Type)
USAGE	Wood, Standstone, Styrene foam and Rough surfaces.  WOOD  SANDSTONE  STYRENE FOAM  ROUGH SURFACES 
REFILABILITY	Non refillable
FEATURES	Writes on a various surfaces. A thick opaque paint ink ensures markings can be seen from a distance and won't fade over time. UV resistant
TOXIC INK CONTENTS	Xylene free

* COMPOSITION

INK	TYPE	Oil based pigment ink
	COLOURS	2 colours (White and Black)
	CONTENTS	8.0 ml
HOLDER		PBT
INK AGITATOR		Carbon steel ball 1 ball (Black), 2 balls (White)
CAP		PBT
BODY		Aluminium
NIB	SHAPE	Bullet style
	MATERIAL	Acrylic fibre

* QUALITY CONTROL

REGULATION	Adapted to the BS safety cap standard and RoHS.
PRODUCTION LOT	Inkjet printing on the bottom face of barrel.

PRODUCT INFORMATION

date :11 July, 2018



* PERFORMANCE

WRITING WIDTH		2.3 mm
WRITING DISTANCE		White: 320-340m by hand writing (Distance may vary with colours) WRITING TEST METHOD : angle 65°, weight 50 g, speed 7 cm per sec., on OHP film
DRYING TIME	WRITING LINE	1 - 2 minutes on PET film
WATER RESISTANCE		Very good
FADE PROOF		Very good
CAUTIONS		* Shake well with cap before use and depress the tip several times to get sufficient ink flow. * Marker is to be used for marking and drawing only. Do not use for other purposes. * Do not drop to avoid ink leaking. * Ink (stain) on cloth may not be removed. * Must be kept out of reach of children. * Harmful if swallowed. Vapor harmful. Avoid contact with eyes or skin. If swallowed and contacted with eyes, call physician immediately. * Keep room well ventilated, when in long use. * Keep capped horizontally when not in use. * Flammable. Do not use or store near heat of flame and throw marker into fire.