

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

REINER

Trade name : REINER Stamping Ink R343 - for Foam and Felt
black
Revision date : 21.04.2021
Print date : 21.04.2021

Version (Revision) : 7.0.2 (7.0.1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

REINER Stamping Ink R343 - for Foam and Felt
black (8050040-005)
Unique Formula Identifier (UFI): K VX8-TK58-30F4-HK2V

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial marking ink

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Reiner GmbH & Co. KG

Street : Baumannstraße 16

Postal code/city : 78120 Furtwangen

Telephone : 07723 / 657-0

Telefax : 07723/657200

Information contact : E-Mail: info@reiner.de

1.4 Emergency telephone number

Poison emergency centre +49-551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

2.2 Label elements

None

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Hochraffiniertes Mineralöl ; REACH Registration No. : 01-211-9448343-41 ; EC No. : 920-360-0

Weight fraction : < 15 %
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

Bis(methylcyclohexyl)phthalat ; EC No. : 248-765-1; CAS No. : 27987-25-3

Weight fraction : < 10 %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315

KEROSINE)PETROLEUM), HYDRODESULFURIZED / KEROSINE - UNSPECIFIED ; EC No. : 265-184-9; CAS No. : 64742-81-0

Weight fraction : < 5 %
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

2-(2-BUTOXYETHOXY)ETHANOL ; REACH Registration No. : 01-2119475104-44-xxxx ; EC No. : 203-961-6; CAS No. : 112-34-5

Weight fraction : < 5 %
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Additional information

Full text of H- and EUH-phrases: see section 16.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

REINER

Trade name : REINER Stamping Ink R343 - for Foam and Felt black
Revision date : 21.04.2021
Print date : 21.04.2021

Version (Revision) : 7.0.2 (7.0.1)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove all contaminated clothing.

Following inhalation

Provide fresh air.

In case of skin contact

Wash away with soap and water and rinse.

After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO2) , Extinguishing powder or Water spray jet .

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

None

5.4 Additional information

Cool endangered containers with water in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Remove mechanically, take-up residues with absorbing material.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

REINER

Trade name : REINER Stamping Ink R343 - for Foam and Felt
black
Revision date : 21.04.2021
Print date : 21.04.2021

Version (Revision) : 7.0.2 (7.0.1)

Protective measures

Measures to prevent fire

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Do not leave vessels open, earth storage containers.

Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (TRGS 510) : 10

Further information on storage conditions

Store containers tightly closed in a cool well ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 10 ppm / 67 mg/m³

Peak limitation : 1,5(I)

Remark : Y

Version : 27.10.2020

Limit value type (country of origin) : STEL (EC)

Limit value : 15 ppm / 101,2 mg/m³

Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)

Limit value : 10 ppm / 67,5 mg/m³

Version : 20.06.2019

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Use tightly fitting safety glasses.

Skin protection

Hand protection

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level >= 240 min (4h) EN374

Respiratory protection

Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

General information

The usual precautionary measures for the handling of chemicals have to be observed.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid

Colour : black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

REINER

Trade name : REINER Stamping Ink R343 - for Foam and Felt black
Revision date : 21.04.2021
Print date : 21.04.2021

Version (Revision) : 7.0.2 (7.0.1)

Odour : characteristic

Safety characteristics

Physical state :		Liquid	
Freezing point :		No data available	
Initial boiling point and boiling range :	(1013 hPa) >	140 °C	
Decomposition temperature :	>	200 °C	
Flash point :	>	61 °C	Brookfield
Auto-ignition temperature :		No data available	
Lower explosion limit :		No data available	
Upper explosion limit :		No data available	
Vapour pressure :	(50 °C) <	1100 hPa	
Density :	(20 °C) ~	1,08 g/cm ³	
Solvent separation test :	(20 °C) <	3 %	
Water solubility :	(20 °C)	No data available	
pH :	~	7	
log P O/W :		No data available	
Flow time :	(20 °C) ~	68 s	DIN-cup 4 mm
Odour threshold :		No data available	
Relative vapour density :	(20 °C)	No data available	
Vapourisation rate :		No data available	
Flammable aerosols :		No data available.	
Oxidising liquids :		No data available.	
Explosive properties :		No data available.	

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

None, if handled according to order.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO₂ released. Formation of hydrogen by acids, lyes, moisture possible.

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

REINER

Trade name : REINER Stamping Ink R343 - for Foam and Felt
black
Revision date : 21.04.2021
Print date : 21.04.2021

Version (Revision) : 7.0.2 (7.0.1)

Acute oral toxicity

Parameter : LD50 (Hochraffiniertes Mineralöl)
Exposure route : Oral
Species : Rat
Effective dose : > 5000 mg/kg
Method : OECD 401
Parameter : LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Oral
Species : Rat
Effective dose : 6580 mg/kg

Acute dermal toxicity

Parameter : LD50 (Hochraffiniertes Mineralöl)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg
Method : OECD 402
Parameter : LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Dermal
Species : Rabbit
Effective dose : 4120 mg/kg

Acute inhalation toxicity

Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

Very high mobility in soil with a negligible tendency to leave the sediment.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Do not empty into waters or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Waste codes/waste designations according to EWC/AVV

- 080111

Additional information

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

REINER

Trade name : REINER Stamping Ink R343 - for Foam and Felt
black
Revision date : 21.04.2021
Print date : 21.04.2021

Version (Revision) : 7.0.2 (7.0.1)

code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Water hazard class (WGK)

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Label elements · 03. Hazardous ingredients

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

16.5 Relevant H- and EUH-phrases (Number and full text)

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

REINER

Trade name : REINER Stamping Ink R343 - for Foam and Felt
black
Revision date : 21.04.2021
Print date : 21.04.2021

Version (Revision) : 7.0.2 (7.0.1)

The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
